

49. Conformance with the requirements specified above constitutes Best Available Technology (BAT) for this source in accordance with OAC rule 3745-31-05.
  50. Southdown shall comply with all applicable Ohio EPA hazardous waste and RCRA regulations.
  51. All records required by this permit to install shall be retained on file by Southdown for a period of not less than three (3) years unless otherwise indicated by the Ohio EPA or RAPCA. All records shall be made available to the Director, or any authorized representative of the Director, for review during normal business hours.
  52. Southdown shall provide a duplicate file to the Greene County Library, **Fairborn** Branch, 1 East Main Street, Fairborn, Ohio 45324 which contains a copy of the following records/reports required in ST&C nos. 14, 15, 16, 18, 20, 21, 22, 23, 32, 35, 37, and 47(B). Southdown shall request that the library maintain these records/reports on file at the library for a minimum of three years.
  53. The owner/operator shall comply with any applicable state and federal requirements governing the storage, treatment, transport, and disposal of any waste material generated by the operation of the source.
  54. The air contaminant source identified in this permit may not cause a public nuisance in violation of OAC rule 3745-15-07.
  55. This facility shall submit a monthly report to RAPCA documenting the exceedance of **any** limitation or specification within this permit. The report shall be submitted by the 15th of the following month.
  56. This facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source are subject to **public** disclosure in accordance with OAC rule 3745-49-03.
-

ATTACHMENT No. 1

SOUTHDOWN, INC.  
Fairborn, Ohio

SPECIFICATIONS FOR LIQUID HAZARDOUS WASTE FUEL (LHWF)

Heat Content	8000 Btu/lb minimum
Sulfur	3.0 % maximum
Chlorine	1.6 % maximum
pH	EXTRACT 4 < pH < 11
Viscosity	500 centipoise maximum @ ambient per ASTM D2196-86 or equivalent
Metals:	
Anthony	- 90 ppm maximum
Arsenic	- 20 ppm maximum
Barium	- 2500 ppm maximum
Beryllium	- 10 ppm maximum
Cadmium	- 90 ppm maximum
Chromium	- 1400 ppm maximum
Lead	- 2100 ppm maximum
Mercury	- 9 ppm maximum
Nickel	- 600 ppm maximum
Silver	- 200 ppm maximum
Thallium	- 20 ppm maximum
Zinc	- 3000 ppm maximum
PCBs	- less than 50 ppm

ATTACHMENT No. 2

SOUTHDOWN, INC.  
Fairborn, Ohio

SPECIFICATIONS FOR USED OIL FUEL .

Heat Content .	- 8000 Btu/lb minimum
Sulfur	- 3.0 % maximum
Total Halogens	- 4000 ppm maximum
Metals:	
Arsenic	- 20 ppm maximum
Cadmium	- 90 ppm maximum
Chromium	- 1400 ppm maximum
Lead	- 2100 ppm maximum
PCBs	- less than 50 ppm

Used oil containing **more than** 1000 ppm total **halogens** is presumed to be a hazardous waste **under** the rebuttable presumption provided **in 40 CFR Part 266.40(c)**. If any used oil received by Southdown is a hazardous waste, it must be managed as **hazardous** waste fuel under this **permit**.